



A Brand of **IRVING** Devcon

30 Endicott St.
Danvers, MA 01923 USA
Telephone: 978-777-1100
Toll Free: 800-933-8266

Technical Data Sheet

Permatex® Nickel Anti-Seize Lubricant

INDUSTRIAL

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Nickel Anti-Seize Lubricant is a high temperature, high quality, heavy duty lubricant that resists galling and corrosion and reduces wear in heavy pressure applications. It contains tenacious metals, oils and graphite materials that cannot be burned away or removed by slow moving parts. This product withstands temperatures ranging from -65°F to 2400°F (-54°C to 1316°C). It is recommended for use where copper contamination must be avoided, under conditions of extreme pressure and temperature and with stainless steel, titanium and nickel alloys.

PRODUCT BENEFITS

Permatex® Nickel Anti-Seize was designed specifically for use on stainless steel or similar alloys. It protects threaded fasteners and fittings from heat, freezing, seizure or galling at temperatures from -65°F to 2400°F. It may be used on pumps, sensors, valves, nuts and bolts where extreme conditions of heat exist.

TYPICAL APPLICATIONS

Drop forge dies and hammers, catalyst bed and reaction chamber supports, slow rotating bearings in hot corrosive environments, lubricate and seal pipe threads in acid environments, coat gaskets in high temperature applications, lubricate conveyor chains, chemical plant bolts for pump housing and pipe flanges.

DIRECTIONS FOR USE

1. Clean mating surfaces before application.
2. For best results, apply to clean, dry surfaces.
3. Clean surfaces with Permatex® Brake & Parts Cleaner.
4. Wire brush any loose surface rust.
5. Apply Nickel Anti-Seize to the parts that require protection.
6. Reassemble parts using normal torque values.
7. Wipe off excess material.

For Cleanup

1. Clean parts with disposable towel.
2. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Mineral oil, nickel, graphite
Appearance	Gray paste
Odor	Petroleum
Specific Gravity	1.1
Temperature Range, °C (°F)	-54(-65) to 1316(2400)
Viscosity, cPs	200,000 (base)
Flash Point, °C(°F)	93(200)
NFPA 704 Flammability Rating	1

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
77124	8 oz. brush-top bottle
77164	16 oz. brush-top bottle

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8°C to 28°C (46°F to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX) Revised 10/02